

ROCH - 30W

PRODUCT HIGHLIGHTS

- · Aesthetically designed cylindrical power track mounted-accent luminaire
- Specially engineered 355° rotatable luminaire and 180° adjustable light head
- The complete luminaire is made of extruded aluminium
- High efficient passive cooling extruded aluminium light head
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°,24°,36°
- High efficacy chip on board (COB) LED technology
- · Adaptor based inbuilt high efficiency electronic driver technology
- Adaptor-suitable for 3 wire & 4 wire power track
- Shade: powder coated-white, black

TECHNICAL SPECIFICATIONS

Light Source	: COB- Chip on Board	
Power Consumption	: 30W	
Color Temperature	: 4000 K	
Driver	: Constant Current AC - DC	
Input voltage range	: 220 - 240 V	
Output voltage	: 33V - 37V DC	
Output Current	: 700 mA	
Power Factor	: >0.98	
THD	: <10%	

LIZZY - 30W

PRODUCT HIGHLIGHTS

- · Aesthetically designed linear profile pendant luminaire for down light and up-light application
- Luminaire housing made from high-grade extruded aluminum
- Profile with provision for running power track system to accentuate light from top side
- High efficiency passive cooling technology for good thermal Management
- Aesthetically designed high efficiency pc symmetric diffuser.
- · High efficacy SMD (Mid Powder) LED technology used in FR-4 PCB
- Inbuilt-high efficiency electronic driver technology
- · Pendent installation with wire-suspender and ceiling coupler
- · Shade: powder coated-black, white, grey

TECHNICAL SPECIFICATIONS

Light Source	: MPL- Mid Power LED		
Power Consumption	: 30W		
Color Temperature	: 4000 K		
Driver	: Constant Current AC - DC		
Input voltage range	: 220 - 260 V		
Output voltage	: 24V - 36V DC		
Output Current	: 400 mA		
Power Factor	: >0.98		
THD	: <10%		

LED KEY ASPECTS

PRODUCT ROCH	WATTS 30W	CRI 90	COLOR TEMP. 4000 K	LUMEN 2773 lm

Color choice













COB











Product Application: